

		<p>3281 - Guasti Road, Suite 260          Ontario, CA 91761          (909) 987-0550 (800) 538-3091          Fax: (909) 987-0490  <a href="http://www.supergluecorp.com">http://www.supergluecorp.com</a></p> <hr/> <p><b>Rear View Mirror Adhesive</b></p>
---	---	--

Pacer Technology Super Glue's Rear View Mirror Adhesive (14104, 15193) is a two-part system used for bonding rear view mirror brackets to windshields and for:

- Glass to metal
- Glass to glass
- Metal to metal

**PROPERTIES:**

Appearance: Part A – Activator/Accelerator – light blue transparent liquid  
 Part B – Adhesive – yellow liquid adhesive  
 Tensile Shear Strength (steel to steel): 2000 – 3000 psi

**DIRECTIONS:** Use in a well-ventilated area. Mark location on outside of windshield with removable marker. Make sure bracket is positioned correctly. Refer to card for proper opening instructions.

1. Apply Activator to both surfaces. Allow 1 minute to dry.
2. Apply 2 drops of adhesive to metal surface to be bonded.
3. Mate parts together using sufficient pressure to spread adhesive. Hold parts together firmly for 1 minute. Allow 1 hour before handling. Full strength develops in 24 hours. For optimum results, wait overnight before attaching mirror to bracket.

**STORAGE AND SHELF LIFE**

Store in cool area away from sunlight or heat. Stored under these conditions, a one-year shelf life can be expected.

**SAFETY AND HANDLING PRECAUTIONS**

Activator – Contains isopropyl alcohol. CAUTION: Flammable. Irritating to eyes. Mild skin irritant. Do not ingest. If swallowed seek medical advice immediately and show this container label. Use and store in well-ventilated area. **KEEP OUT OF REACH OF CHILDREN.**

Adhesive – Contains methacrylate esters and acrylic acid. CAUTION: Irritating to eyes and skin. May cause sensitization by skin contact. Avoid contact with skin & eyes. In case of eye contact, rinse immediately with water for 15 minutes and seek medical advice. For skin contact, wash well with soap and water. If swallowed seek medical advice immediately and show this container label. **KEEP OUT OF REACH OF CHILDREN.**

For more information, refer to Material Safety Data Sheet available upon request or obtain from our Pacer Technology website @ [www.supergluecorp.com](http://www.supergluecorp.com). In case of emergency, call CHEMTREC at (800) 424-9300 or call Pacer Technology (800) 538-3091 (outside CA only) or (909) 987-0550.

Rev 1 – 2016 kr

The information in this Product Data Sheet (PDS) is of a general nature based on our knowledge and experience with this product and should be used for information and consideration purposes only. The product can have a variety of different applications, as well as differing application and working conditions in your environment that are beyond our control. Therefore, this data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which Pacer Technology assumes legal responsibility. Pacer Technology strongly recommends that users of the product independently determine the suitability of the product for their use.

Pacer Technology specifically disclaims any liability for consequential or incidental damages of any kind, including profit. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial, and local laws and regulations.