

		<p>3281 - Guasti Road, Suite 260 Ontario, CA 91761 (909) 987-0550 (800) 538-3091 Fax: (909) 987-0490 http://www.supergluecorp.com</p> <p style="text-align: center;">Steel Repair & Filler</p>
---	---	--

Pacer Technology Super Glue Steel Repair & Filler (T-SR) is a single component adhesive that can be used to repair holes and cracks on any steel or steel alloy object. This product can be drilled, filled or sanded after cure, is resistant to boiling water, to oil and gasoline, and is best used for:

- Pipes
- Car radiators
- Mufflers
- Kettles
- Household objects

PROPERTIES:

<u>Initial color:</u> Dark gray	<u>Full Strength:</u> 24 hours
<u>Final color:</u> Dark gray	<u>Operating Temperature Range:</u> 25 ⁰ to 200 ⁰ F
<u>Tack-free time:</u> Less than 10 minutes	(-4 ⁰ to 93 ⁰ C)
<u>Dry Time:</u> 3-4 hours	

Note: Product not recommended for drinking water applications.

USE INSTRUCTIONS: Use in a well-ventilated area. Protect work surfaces. Clean and dry surfaces. Roughen surface for stronger bond strength.

1. Apply product directly from tube to repair area. For large repairs or deep holes, apply in layers, allowing each layer to dry before applying the next.
2. Allow 3-4 hours for drying. Full strength is in 24 hours. Recap product for storage.

STORAGE AND SHELF LIFE

Store in cool area away from sunlight or heat. Stored under these conditions, a one-year shelf life can be expected.

SAFETY AND HANDLING PRECAUTIONS

Contains acetone, isopropyl alcohol and methyl ethyl ketone. DANGER: Extremely flammable. Vapor harmful. Irritating to eyes and skin. Use and store in well-ventilated area away from heat, sparks or flames. Avoid eye contact and prolonged contact with skin. In case of eye contact, flush thoroughly with water for 15 minutes and get medical attention. If swallowed, do not induce vomiting; seek medical advice immediately and show this container label. **KEEP OUT OF REACH OF CHILDREN.**

For more information, refer to Material Safety Data Sheet available upon request or obtain from our Pacer Technology website @ www.supergluecorp.com. In case of emergency, call CHEMTREC at (800) 424-9300 or call Pacer Technology (800) 538-3091 (outside CA only) or (909) 987-0550.

Rev 1 – 2016 kr

The information in this Product Data Sheet (PDS) is of a general nature based on our knowledge and experience with this product and should be used for information and consideration purposes only. The product can have a variety of different applications, as well as differing application and working conditions in your environment that are beyond our control. Therefore, this data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which Pacer Technology assumes legal responsibility. Pacer Technology strongly recommends that users of the product independently determine the suitability of the product for their use.

Pacer Technology specifically disclaims any liability for consequential or incidental damages of any kind, including profit. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial, and local laws and regulations.