



Minute Mend™ Epoxy Putty, 4 Wt Oz

No. 14070 | Item# 1004796 | Case# 1004795

| | |
|---------------------------|---|
| Product Description | This two part epoxy permanently repairs scratches, gouges and holes. Bonds to wood, steel, fiberglass, glass, ceramics, plastics, concrete and aluminum. Also bonds to both wet and dry surfaces. It is ready to use in less than one minute. |
| Applications | Drums, tanks, castings, molds, sinks, tubs, gaskets, mounting terminal blocks, packing wires & repairing breaker boxes |
| Unit Package Description | 4 ounce Stick |
| Brand | CRC |
| Generic Description 1 | Epoxy Putty |
| Net Fill | 4 Wt Oz |
| UPC Code | 078254140704 |
| Unit Dimensions | 8H x 1W x 1D in |
| Units Per Case | 24 |
| Case Dimensions | 9.06H x 5.5W x 7.13D in |
| Cases Per Pallet | 144 |
| Case Weight | 8 lbs |
| I 2 of 5 Code | 30078254140705 |
| Appearance | Green and White Putty |
| Flash point (F) | >200°F |
| Flash point (C) | >93.3°C |
| Flammability Class - CPSC | None |
| Spec Gravity Concentrate | 1.97 |
| Plastic Safe | Safe on Most Plastics (Test small area) |
| Evaporation Rate | Negligible |
| Curing Time | 24 Hours |
| Dielectric Strength | 300 Volts/Mil |
| Working Temp (F) | 250°F (Continuous) / 350°F (Intermittent) |
| Working Temp (C) | 121°C (Continuous) / 176.66°C (Intermittent) |

Last revised: 10/8/2019

Page 1 of 2



Chemical Solutions to Keep You Moving™

f t+ in • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



| | |
|---------------------------------|---|
| Propellant | None |
| DOT Proper Shipping Name | Not Regulated |
| VOC % (Consumer Product def) | 0 |
| VOC g/L (Consumer Product def) | 0 |
| VOC lbs/gal (Consumer Prod def) | 0 |
| VOC Category | Sealant or Caulking Compound, chemically curing, nonaerosol |
| Removal (How To) | Cured Material: Heat to Soften |