



Accept



## CRC Dry Graphite Lube

### ATTRIBUTES -

<b>Item Number</b>	1003362
<b>Case Number</b>	1003361
<b>Legacy Number</b>	03094
<b>Product Description</b>	Ideal where a dry lubricant is required or where petroleum products must be avoided. Resists dirt, dust and oil build-up. Wide effective temperature range up to 850°F constant.
<b>Applications</b>	Gaskets, transfer belts, conveyor belts, motors, plant machinery and handling equipment, rubber moldings, high temperature, low load, or high rpm slides, rollers, wheels, gears, chains & hoists
<b>Unit Package Description</b>	16 Ounce Aerosol
<b>Brand</b>	CRC
<b>Net Fill</b>	10 wt oz
<b>UPC Code</b>	078254030944
<b>Unit Dimensions</b>	7.75H x 2.63W x 2.63D in
<b>Units Per Case</b>	12
<b>Case Dimensions</b>	8.69H x 8.44W x 11.31D in
<b>Cases per pallet USA</b>	133
<b>Appearance</b>	Black Liquid
<b>Flash point (F)</b>	-4°F
<b>Flash point (C)</b>	-20°C
<b>Flammability Class - CPSC</b>	Extremely Flammable
<b>Spec Gravity Concentrate</b>	0.81
<b>KB Value</b>	N/A
<b>Plastic Safe</b>	No
<b>Film Type</b>	Dry
<b>Evaporation Rate</b>	Moderate
<b>Timken Ok Load (lbs)</b>	N/A
<b>Propellant</b>	Hydrocarbon
<b>Aerosol Flammability Level</b>	III
<b>DOT Proper Shipping Name</b>	Aerosols, Flammable, LIMITED QUANTITY
<b>4 Ball EP</b>	Not Determined
<b>4 Ball Wear</b>	Not Determined
<b>Drop Point</b>	N/A
<b>pH</b>	N/A
<b>SAE Grade</b>	N/A
<b>Water Washout</b>	N/A
<b>Working Temp (F)</b>	400°F (Continuous) / 850°F (Intermittent)
<b>Working Temp (C)</b>	204°C (Continuous) / 454°C (Intermittent)
<b>VOC % (Consumer Product def)</b>	48.6
<b>VOC g/L (Consumer Product def)</b>	388.8
<b>VOC lbs/gal (Consumer Prod def)</b>	3.24
<b>VOC Category</b>	Dry Film Lubricant
<b>Removal (How To)</b>	Remove with petroleum solvents.

