



Accept



CRC Heavy Duty Silicone Lubricant

ATTRIBUTES –

Item Number	1003743
Case Number	1003741
Legacy Number	05174
Product Description	Lubricates and eliminates squeaking and binding caused by friction. Film is clean, odorless, and highly resistant to water. Use on nylon, rubber, metal & non-metal surfaces.
Applications	Wood, metal and rubber surfaces. Use in moist and harsh environments. Not for use as an appearance cleaner or on paint.
Unit Package Description	16 Ounce Aerosol
Brand	CRC
Net Fill	11 wt oz
UPC Code	078254051741
Unit Dimensions	7.75H x 2.63W x 2.63D in
Units Per Case	12
Case Dimensions	8.13H x 5.47W x 8.00D in
Cases per pallet USA	133
Appearance	Clear Colorless Liquid
Base Type	Silicone
Flash point (F)	<0°F
Flash point (C)	<-18°C
Flammability Class - CPSC	Extremely Flammable
Spec Gravity Concentrate	0.748
KB Value	N/A
Plastic Safe	No
Film Type	Thin, Dry
Film Thickness	Non-Drying
Evaporation Rate	Fast
Dielectric Strength	350 Volts/Mil
Timken Ok Load (lbs)	N/A
Propellant	Hydrocarbon
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
4 Ball EP	N/A
4 Ball Wear	N/A
Drop Point	N/A
pH	N/A
ISO Viscosity Grade	N/A
NLGI Grade	N/A
SAE Grade	N/A
Water Washout	N/A
Working Temp (F)	-40 to 400°F
Working Temp (C)	-40 to 204.4°C
VOC % (Consumer Product def)	59.5
VOC g/L (Consumer Product def)	445.1
VOC lbs/gal (Consumer Prod def)	3.7
VOC Category	Silicone Based Multi-Purpose Lubricant
Removal (How To)	Remove with soap & water, CRC HydroForce® All Purpose, etc. and elbow power (scrubbing).

